


Suitable for insert 07-serie

DESCRIPTION
 Travel : 90° ±5° At both ends.
 Ratio : 35 : 1
 Turns to close : 8.75
 Weight : 7.3 kg (16.2 lb.) Excl.handwheel

MOUNTINGHOLES
 Valve connection : F05-F07
 MAX. bore : $\phi 17 [0.67]$ or $\phi 20 [0.79]$
 Actuator connection : F05-F07
 MAX. shaft : $\phi 30 [1.18]$ or $\phi 42 [1.65]$

TORQUE
 max.OUTPUT : 250 Nm (2210 lbf.in.)
 max.INPUT : 26 Nm (230 lbf.in.)
 M.A. : 9.5 ±15%




Dimensions in MM [Inch]

rotork gears
 Nijverheidstraat 25
 7561 Loozer
 The Netherlands

GEARBOX ILG/D 200

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.V Date : 15-11-'05
 Dwg Nr.: D92N-002 Rev.: 02

Contents Subject to change without notice.