


3/2 Relief valve  
(optional)

Suitable for 240-series insert

DESCRIPTION	
Travel	: 5° to 95° adjustment
Ratio	: 68 : 1
Turns to Close	: 17
Weight	: 54 Kg (118.8 Lb) Incl. Handwheel

MOUNTINGHOLES	
Valve connection	: F12/F14/F16
MAX. bore	: $\phi 46 [1.81]$ or $\phi 55 [2.20]$
Actuator connection	: F14/F16
MAX. shaft	: $\sqrt{62 [2.44]}$ or $\phi 88 [3.46]$

TORQUE	
Max. Output	: 3390 Nm (30000 lbf in.)
Max. Input	: 188 Nm (1665 lbf in.)
M.A.	: 18 ± 15%



**rotork gears**

Nijverheidstraat 25  
7135  
The Netherlands

# GEARBOX ILG/D 2400

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY WITHOUT THE WRITTEN PERMISSION OF ROTORK GEARS. ACKNOWLEDGEMENT OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS.

Drawn : N.M	Date : 05-06-06
Dwg Nr.: D96N-001	Rev.: 05

Contents Subject to change without notice.