


Suitable for 10-series insert

DESCRIPTION	
Travel Ratio	: 5° to 95° adjustment
Turns to Close	: 46 : 1
Weight	: 17 Kg. (37.7Lb) Excl. Handwheel

MOUNTINGHOLES	
Valve connection	: R07 / F10 / F12
Max. Bore	: # 27 [1.06] or Ø30 [1.18]
Actuator connection	: R07 / F10 / F12
Max. Bore	: # 34 [1.34] or Ø49 [1.93]

TORQUE	
Max. Output	: 750 Nm (6640 lbf in.)
Max. Input	: 60 Nm (530 lbf in.)
M.A.	: 12.4 ± 15%




**rotork gears**

Nijverheidstraat 25  
7561 N, Loosdrecht  
The Netherlands

**GEARBOX ILG/D 600**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.V.

Date : 15-11-'05

Dwg Nr.: D93N-002

Rev.: 02

Contents Subject to change without notice.